



Photo et textes non contractuels

JET 15 i

(Ref. 20402040)

Water and dust suction

Usage très intensif

Norm: EN 60335-2-69

Guarantee:  3 €

Product Information:

Manual unclogging system of the filter using a single buTon
Water-resistant high-efficiency 9.9% Class M cartridge filter
Metal accessories and stainless steel tubes
Carbon-fibre reinforced base
Storage unit of accessories integrated to the base
Large 2-wheel + 2 castors for a stabilised stability
Anti-crushing shielded hose
By-pass cooling down system 1450W motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)
Suction, depression and cutting-off high-performance
Anti-static electricity plate connected to earth
Neoprene power table HO7 RNF length 7 m

Standard accessories:

- Bent tubes 2 x 500 mm Ø 32 mm
- hose Ø 32 mm, length 2,2 m
- liquid nozzle de 400 mm
- dual-purpose nozzle - 270 mm
- round brush
- flat nozzle
- Padding nozzle
- Class M cartridge filter PTFE

Technical characteristics:

Height (cm) : 60.00
Width (cm) : 42.50
Length (cm) : 46.00
Net weight (Kg) : 13.18
Power (W) 1450
Power (V) 1-phase 230V
Tank stainless steel
Tank capacity (l) 20
Depression (Kpa) 26.7
Flow (l/min) 4 200
Sound level (dBA) 74
Atex Zone 22 No
Accessory diameter (mm) 32
Unclogging Yes
Class-M approved No
Vacuum cleaner filter Class M PET cartridge
Synchro socket No
Cable length (m) 7
Tank capacity (L) 23