



Photo et textes non contractuels

## MC 55 i

(Ref. 20403006)

Water and dust suction

**Usage régulier**

Norm: EN 60335-2-69

Guarantee:  

### Product Information:

"Fitted standard with a class L filter

Anti-crushing shielded hose

4-wheel stand for optimised motion

Dual turbine suction

By-pass cooling motor (air is sucked up by a third turbine on top of the motor, only for cooling down). Designed for heavy-duty jobs

Vinyl power cable H05 VV-F length 7 m

Separate switch per motor

### Standard accessories:

- plastic tubes
- liquid nozzle
- suceur à poussières
- round brush
- flat nozzle
- hose, length 2,7 m Ø 40 mm

### Technical characteristics:

Height (cm) : 92.50

Width (cm) : 52.00

Length (cm) : 52.00

Net weight (Kg) : 23.00

Repairability index 8,8/10

Power (W) 2 x 1000

Power (V) 1-phase 230V

Tank stainless steel

Tank capacity (l) 50

Depression (Kpa) 22.54

Flow (l/min) 7 080

Sound level (dBA) 84

Atex Zone 22 No

Accessory diameter (mm) 40

Unclogging No

Class-M approved No

Vacuum cleaner filter Class L

Synchro socket No

Cable length (m) 7

Tank capacity (L) 78