



Photo et textes non contractuels

## ULTRA ASP 40P-H

(Ref. 20405050)

Suction of water, dust, and wood dust

**Usage intensif spécifique**

Norm: EN 60335-2-69, Classe H

Guarantee:  

### Product Information:

Class H approved vacuum cleaner + asbestos certification  
No-bag water and fine or clogging fine dust suction  
Automatic unclogging system, the filter is automatically unclogged through air pulses, during a 2.2 s cycle every 15 s, without any suction interruption  
Unpluggable unclogging system  
Fitted with an electrical socket to perform a synchronised start using an electroportable tool 100 to 2400 W  
Main PTFE filter: low dust adhesion, rot-proof and washable  
Double filtration secondary filter, HEPA for class H  
Pre-fitted with adaptors for storage box support, Sortimo or Systainer (optional)  
Accessory support  
Support hose  
Power cable support  
Elastic strap to hold the tools  
Anti-crushing shielded hose  
fitted with 2 wheels + 2 brake-swivelling metal castors  
Tank handle  
Smooth motor start through electronic speed variator  
Motor overheat safety device with automatic switching off  
Neoprene power table H05 RR-F 3G 1,5 length 7,5 m  
Antistatic

### Technical characteristics:

Height (cm) : 61.00  
Width (cm) : 38.00  
Length (cm) : 57.00  
Net weight (Kg) : 19.60  
Power (W) 1400  
Power (V) 1-phase 230V  
Tank Polypropylene  
Tank capacity (l) 29,5  
Depression (Kpa) 25  
Flow (l/min) 4500  
Sound level (dBA) 60  
Atex Zone 22 No  
Accessory diameter (mm) 36  
Unclogging automatic  
Class-H approved Yes  
Vacuum cleaner filter Class M PTFE + HEPA for Class H  
Synchro socket Yes  
Cable length (m) 7,5  
Tank capacity (L) 42

### Standard accessories:

- Bent stainless steel tube 400 mm
- Straight stainless steel tubes 2 x 500 mm
- hose Ø 36 mm, length 4 m
- water and dust nozzle 400 mm
- flat nozzle 200 mm
- Class M PTFE flat main filter
- Secondary filter HEPA for class H
- Double bagging safety bag
- Power tool adapter