



Photo et textes non contractuels

## 16 FV

(Ref. 20502079)

Drilling, milling metals, plastic materials and wood  
**Usage régulier**

Guarantee:  

### Product Information:

Steel cast iron frame, head and stand  
Dovetail column  
Emergency Stop through mushroom stay put button  
Left and right tilting column  
Slow down motion  
Servo polycarbonate screen  
Cross-motion table  
Table grooving  
Electronic speed variator  
Brushless motor

### Deliver with:

- Key less 16 mm chuck
- Chuck tail
- Vice

### Technical characteristics:

Height (cm) : 72.00  
Width (cm) : 60.00  
Length (cm) : 57.00  
Net weight (Kg) : 71.00  
Power(kW) 0,5  
Power (V) 1-phase 230V  
Spindle speed (rpm) 100 : 2500  
Max. drilling capacity (mm) 16  
Milling capacity (mm) 35  
Morse taper MT3  
Spindle stroke (mm) 180  
Number of gears Variable  
d: spindle/column distance (mm) 165  
f: spindle/table distance (mm) 90 à 270  
Table dimension (mm) 460 x 120  
Distance between table grooves (mm) 35  
Lighting No  
Servo screen Yes  
Reversible vice table No  
Coolant No  
Transversal / longitudinal stroke (mm) 135 x 460  
Automatic down motion (mm/tr) No  
Slow down motion Yes  
Semi automatic tapping No  
Cross motion table Yes