



## 25 FV

(Ref. 20502080)

Drilling, tapping, milling metals, plastic materials and wood,  
(coolant is optional)

**Usage intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Steel cast iron frame, head and stand  
Dovetail column  
Emergency Stop through mushroom stay put button  
Semi automatic tapping system on handles and instant return  
Left and right tilting milling head  
Slow down motion  
Servo polycarbonate screen  
Cross-motion table, stroke 145 x 400 mm  
Table grooving - distance between centers 45 mm  
Electronic speed variator  
Digital display of the spindle speed et de la profondeur de perçage

### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- rapid-clamping vice 100 mm
- Without stand

### Technical characteristics:

Height (cm) : 85.00  
Width (cm) : 73.00  
Length (cm) : 76.00  
Net weight (Kg) : 181.00  
Power(kW) 1  
Power (V) 1-phase 230V  
Spindle speed (rpm) 100 : 1800  
Max. drilling capacity (mm) 25  
Max. tapping capacity (mm) M12  
Milling capacity (mm) 50  
Morse taper MT3  
Spindle stroke (mm) 70  
Number of gears Variable  
d: spindle/column distance (mm) 235  
f: spindle/table distance (mm) 380  
Table dimension (mm) 550 x 160  
Distance between table grooves (mm) 45  
Lighting No  
Servo screen Yes  
Reversible vice table No  
Coolant No  
Transversal / longitudinal stroke (mm) 145 x 400  
Automatic down motion (mm/tr) No  
Slow down motion Yes  
Semi automatic tapping Yes  
Cross motion table Yes