



PRO 30FV

(Ref. 20502091)

Drilling, tapping, milling metals, plastic materials and wood, (with coolant)

Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Massive steel cast iron bed, head and base
Adulid-tailed prismatic column
6 speed per mechanical gearbox
Semi-automatic tapping system - instant return
Fine feed
Cross-moving table
Gear head $\pm 45^\circ$ swiveling
Very low voltage controls 24 V
Stop punch to hook
3-point locking sectioner
LED lighting 24 V

Supplied with:

- Stand
- Toolbox
- Service key set
- Set of 42 flanges
- Self-tightening 16 mm mandrin
- Chuck arbor
- Drift key
- Vice 125 and clamps

Technical characteristics:

Height (cm) : 200.00
Width (cm) : 95.00
Length (cm) : 100.00
Net weight (Kg) : 385.00
Power(kW) 1.5
Power (V) 1-phase 230V
Spindle speed (rpm) 100 : 1600
Max. drilling capacity (mm) 30
Max. tapping capacity (mm) M16
Milling capacity (mm) 55
Morse taper MT4
Spindle stroke (mm) 85
Number of gears Variable
d: spindle/column distance (mm) 270
f: spindle/table distance (mm) 430
Table dimension (mm) 820 x 240
Distance between table grooves (mm) 3 x 55
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant No
Jaw width (mm) 125
Jaw height (mm) 30
Opening (mm) 105
Transversal / longitudinal stroke (mm) 450 x 245
Automatic down motion (mm/tr) No
Slow down motion Yes
Semi automatic tapping Yes
Cross motion table Yes