



## SPC 32 TE

(Ref. 20601126)

Drilling metals, plastic materials and wood, with coolant  
**Usage très intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Steel cast iron frame, head and stand
- Steel column
- Machined aluminium pulleys
- Transmission through V belts with rapid adjustment of tension
- Spindle fitted on bearings
- Adjustable spindle rack motion through return spring
- 2-gear motor
- 24V very low voltage controls
- ON/OFF
- Switching on lamp
- Emergency Stop through mushroom stop button
- 3-point locking circuit breaker
- Detachable servo protective shield
- 24V lighting
- Electrical protection IP54
- Noise level 50 dB
- 3-position reversible vice table (with vernier), V jaws to drill tubes
- Vice fitted on guideways to center the part to drill
- Rack-driven table, graisseur de la vis sans fin
- Hot weather adaptation on request
- Can be modified to 230V three-phase on request

### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

### Technical characteristics:

- Height (cm) : 180.00
- Width (cm) : 43.50
- Length (cm) : 88.00
- Net weight (Kg) : 290.00
- Power(kW) 0.6/1.1
- Power (V) 3-phase 400V
- Spindle speed (rpm) 35-1980
- Max. drilling capacity (mm) 32
- Morse taper MT3
- Column dia (mm) 110
- Spindle stroke (mm) 110
- Number of gears 14
- d: spindle/column distance (mm) 280
- e: spindle/base distance (mm) 1 210
- f: spindle/table distance (mm) 50-630
- Table dimension (mm) 350 x 350
- Distance between table grooves (mm) 130
- Lighting Yes
- Servo screen Yes
- Reversible vice table Yes
- Coolant Yes
- Jaw width (mm) 100
- Jaw height (mm) 30
- Opening (mm) 100
- Automatic down motion (mm/tr) No
- Slow down motion No
- Semi automatic tapping No
- Cross motion table No