

FORETS HSS 5% COBALT

(Ref. 11500000)

Drilling of steels, stainless steels, and cast irons
Usage intensif

Photo et textes non contractuels

Product Information:

Box of 25 HSS metal drills
Split-point grinding:reduction of the drill tip. Enables the simple self-centri ng of the drill bit on the smoothest of surfaces. Significantly reduces the r equried axial load.
135° tip: 135° tip angle for the sharpening of the drill bit. Suitable for stro ng and difficult materials. Enables a shorter and stronger cutting edge, th us prolonging the service life.
Cylindrical shank: the diameter of the shank is equal to the diameter of th e tip. Enables versatile use on portable electrical tools and machine tools.
30° type N flute: normal flute profile with a 30° helix angle. Suitable for ge neral use. Provides good rigidity to the tool, as well as excellent drilling pr ecision.
5% cobalt high-speed steel: HSS substrate enriched with 5% cobalt. Impro ved heat retention (strength, cutting sharpness). For general use in metals up to 1200 N/mm².

Technical characteristics:

Height (cm) : 6.00
Width (cm) : 11.50
Length (cm) : 20.00
Net weight (Kg) : 1.18
For machine Floor machine drill, portable drill
Characteristic 1 Box of drill bits HSS 5% cobalt
Diameter (mm)
Shank (mm) Cylindrical