

JET 30

(Ref. 20402008)

Water and dust suction
Usage très intensif

Norm: EN 60335-2-69
Guarantee: 3 ans CE

Photo et textes non contractuels

Product Information:

"Fitted with a higk-eeficiency 99.9% Class M filter
Metal accessories and stainless steel tubes
Anti-crushing shielded hose 4-wheel stand for optimised motion
Dual turbine suction
By-pass cooling down system motor designed for continuous heavy-duty j obs (air is sucked by a third turbine on top of the motor, only for cooling d own)
Anti-static electricity plate connected to earth
Neoprene power table HO7 RNF length 7 m

Standard accessories:
- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 2.5 m
- Dust nozzle - 400 mm
- liquid nozzle - 400 mm
- round brush
- flat nozzle
- round brush fitting
- Class M filter

Technical characteristics:

Height (cm) : 73.00
Width (cm) : 40.50
Length (cm) : 40.50
Net weight (Kg) : 14.00
Power (W)
Power (V) 1-phase 230V
Tank stainless steel
Tank capacity (l)
Depression (Kpa) 23.52
Flow (l/min) 3 600
Sound level (dBA)
Atex Zone 22 No
Accessory diameter (mm)
Unclogging No
Class-M approved No
Vacuum cleaner filter Class M
Synchro socket No
Cable length (m)
Tank capacity (L)