



MC 16 i

(Ref. 20403004)

Water and dust suction

Usage régulier

Norm: EN 60335-2-69

Guarantee:  

Photo et textes non contractuels

Product Information:

- Fitted standard with a class L filter
- Anti-crushing shielded hose
- 4-wheel stand for optimised motion
- Dual turbine suction
- By-pass cooling motor (air is sucked up by a third turbine on top of the motor, only for cooling down)
- Motor designed for heavy-duty jobs
- Vinyl power cable H05 VV-F length 7 m

Standard accessories:

- telescopic steel tube Ø 32 mm
- dual-purpose dust nozzle
- liquid nozzle
- round brush
- flat nozzle
- padding nozzle
- hose, length 2,6 m Ø 32 mm

Technical characteristics:

- Height (cm) : 58.00
- Width (cm) : 40.00
- Length (cm) : 40.00
- Net weight (Kg) : 11.00
- Repairability index
- Power (W)
- Power (V) 1-phase 230V
- Tank stainless steel
- Tank capacity (l)
- Depression (Kpa) 22.54
- Flow (l/min) 3 530
- Sound level (dBA) 69.5
- Atex Zone 22 No
- Accessory diameter (mm)
- Unclogging No
- Class-M approved No
- Vacuum cleaner filter Class L
- Synchro socket No
- Cable length (m)
- Tank capacity (L)