

# 30 CV

(Ref. 20502022)

Drilling and tapping of metals, plastic materials and wood, with coolant
**Usage intensif**

Guarantee: 3 ans

**Photo et textes non contractuels**

## Product Information:

Steel cast iron frame, head and stand
Steel column
Spindle fitted on bearings
24V very low voltage controls
Emergency Stop through mushroom stay put button
Locking main switch 4 points
Semi automatic tapping system + instant return
Servo detachable chuck protective shield
Large table mécanicien, Rack-driven table
Electronic speed variator
Digital display of the spindle speed
LED ligthing 24 V

**Supplied with:**
- Tap-holder chuck M3 to M16
- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- BSH 7 vice and set of clamps

## Technical characteristics:

Height (cm) : 176.50
Width (cm) : 52.50
Length (cm) : 66.00
Net weight (Kg) : 220.00
Power(kW)
Power (V) 3-phase 400V
Spindle speed (rpm)
Max. drilling capacity (mm)
Max. tapping capacity (mm)
Morse taper MT3
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm) 1 150
f: spindle/table distance (mm)
Table dimension (mm)
Distance between table grooves (mm)
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant Yes
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping Yes
Cross motion table No