

# PRO 22 PEVT

(Ref. 20502085)

Dry drilling of metals, plastic materials and wood (optional lubrication)
**Usage intensif**

Guarantee: 3 ans

**Photo et textes non contractuels**

## Product Information:

Steel cast iron frame, head and stand
Steel column
Transmission through Poly V belts with tension adjustment
Spindle fitted on bearings
Adjustable spindle mack motion through retiurn spring
Drilling-depth stop
Semi automatic tapping system
Electronic speed variator
Digital display of the spindle speed
Emergency Stop through mushroom stay put button
Safety microswitch of the pulley cover

Spindle speed override buTon
Servo detachable chuck protective shield
LED ligthing 3.6 V - 3 W
Tilting table up to 45ø with a vernier and a coolant collector + 12-mm tabl e grooves
Rack-driven table

**Supplied with:**
- Tap chuck M3 to M12
- Key-less chuck 16 mm
- Chuck shank
- Taper drift
- Vice BSF 120 and clamp set

## Technical characteristics:

Height (cm) : 108.50
Width (cm) : 72.00
Length (cm) : 37.00
Net weight (Kg) : 101.68
Power(kW)
Power (V) 1-phase 230V
Spindle speed (rpm)
Max. drilling capacity (mm)
Max. tapping capacity (mm)
Morse taper MT2
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm)
f: spindle/table distance (mm)
Table dimension (mm)
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant No
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping Yes
Cross motion table No