

Photo et textes non contractuels

EXPERT 30 PC

(Ref. 20502105)

Dry drilling of metals, plastic materials and wood (optional lubrication)
Usage régulier

Guarantee: 3 ans CE

Product Information:

Steel cast iron column
Transmission through steel dented belt and wheels
Spindle fitted on bearings
ON/OFF switch fitted with a lack of voltage coil
Emergency Stop through mushroom stay put button
Protective shield of servo chuck
Tilting table up to 45ø, avec récupérateur de liquide de coupe
Rack-driven table
Digital readout of the drilling depth
Digital display of the spindle speed
Drilling-position laser
LED ligthing
Pulley cover fitted with a grip-safety microswitch

Supplied with:
- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

Technical characteristics:

Height (cm) : 174.00
Width (cm) : 43.00
Length (cm) : 77.00
Net weight (Kg) : 114.00
Power(kW)
Power (V) 3-phase 400V
Spindle speed (rpm)
Max. drilling capacity (mm)
Morse taper MT3
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm) 1 215
f: spindle/table distance (mm)
Table dimension (mm)
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant No
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No