

SPC 32 TE VEL T

(Ref. 20601125)

Drilling metals, plastic materials and wood, with coolant
Usage très intensif

Guarantee: 3 ans CE

Photo et textes non contractuels

Product Information:

Steel cast iron frame, head and stand
Steel column
Machined aluminium pulleys
Transmission through V belts with rapid adujstment of tension
Spindle fitted on bearings
Adjustable spindle mack motion through retiurn spring
24V very low voltage controls
ON/OFF
Switching on lamp
Emergency Stop through mushroom stay put button
3-point locking circuit breaker
Detachable servo protective shield
24V lighting
Semi automatic tapping
Electronic speed variator
Electrical protection IP54
Noise level 50 dB
3-position reversible vice table (with vernier), V jaws to drill tubes
Vice fitted on guideways to center the part to drill
Rack-driven table, graisseur de la vis sans fin
Hot weather adaptation on request
Can be modified to 230V three-phase on request

Supplied with:
- Tap-holder chuck M3 to M16
.- Self-clamping chuck 16 mm
- Chuck shank

Technical characteristics:

Height (cm) : 180.00
Width (cm) : 43.50
Length (cm) : 88.00
Net weight (Kg) : 300.00
Power(kW)
Power (V) 3-phase 400V
Spindle speed (rpm)
Max. drilling capacity (mm)
Morse taper MT3
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm) 1 210
f: spindle/table distance (mm)
Table dimension (mm)
Distance between table grooves (mm)
Lighting Yes
Servo screen Yes
Reversible vice table Yes
Coolant Yes
Jaw width (mm)
Jaw height (mm)
Opening (mm)
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping Yes
Cross motion table No